

# TECHNIC

## standard

Fully adjustable full body harness for rope access, work positioning and fall arrest with Easy-lock buckles and steel components.

### DESCRIPTION

Attachment of the CAM CLEAN chest ascender by a mailon and the CAM CLEAN strap.

Front large attachment point for attaching descender or work positioning devices (EN 813, EN 358).

Steel side positioning points according to EN 358 with position adjustment are placed symmetrically and do not interfere at work.

Easy-lock buckles allow very easy tightening and adjustment of the harness.



Rear attachment point does not interfere with carrying a backpack or breathing apparatus.

Front and rear attachment points for fall arrest (EN 361).

2 braided gear loops with a bearing capacity of 5 kg.

### KEY FEATURES

- the corrosion resistance of the steel components is tested by spraying in a salt chamber for 48 hours

### STANDARDS

## CE 1019

EN 358:2018  
EN 361:2002  
EN 813:2008

### FEATURES



M/L = 1725 g  
M/L = 60.85 oz




3 YEARS warranty

### MATERIALS



- 37 % stainless steel
- 33 % PAD
- 12 % PES
- 10 % EVA foam
- 8 % polyethylene

### TECHNICAL DATA



	S	M/L	XL
A [cm/in]	65-80 / 25-31	75-100 / 29-39	85-130 / 33-51
B [cm/in]	45-60 / 18-24	50-75 / 20-29	50-75 / 20-29
C [cm/ft]	150-170 / 4.92-5.57	160-180 / 5.25-5.9	175-205 / 5.74-6.73

COMPARISON

**TECHNIC standard vs. TECHNIC standard (previous generation)**

- front large attachment point for attaching descender or work positioning devices (EN 813, EN 358)
- the corrosion resistance of the steel components is tested by spraying in a salt chamber for 48 hours



TECHNIC standard

MAINTENANCE

Lifetime of this product depends on the frequency and the environment (salt, sand, moisture, chemicals, etc.) in which is used. Without taking wear or mechanical damage into account and in compliance with the conditions specified in the instructions for use this product may be used 15 years from the date of production and 10 years from the date of the first use. However mechanical damage can occur during the first use, which can limit the lifetime of this products only to its first use.



OTHER VIEWS



Additional slots on the waist belt allow you to safely hang expensive equipment (chainsaw, drill...)

RELATED PRODUCTS



TECHNIC SPEED



TECHNIC ANSI SPEED



TECHNIC ANSI STANDARD



TECHNIC PADDING

SIZE	CODE	SIZE	CODE	SIZE	CODE	SIZE	CODE
S	W0064BB02	S	W0104BB02	S	W0103BB02	UNI	W0097BB00
M/L	W0064BB03	M/L	W0104BB03	M/L	W0103BB03		
XL	W0064BB05	XL	W0104BB05	XL	W0103BB05		